



Stainless Steel Cable Ties- Ball-Lock Fully Polyester Coated Ties

▶ Product Feature

- Fully coated vision will prevent static electricity
- Polyester coated band provide additional edge protection, prevent the corrosion between dissimilar materials.

▶ Technical Information

- Material: Stainless Steel Grade 304, 316, 316L
- Coating: Polyester;Nylon 11
- Working Temp.: -80°C to 150°C
- Description: Entirely Black
- Flammability: Fireproof
- Other Properties: UV-resistant, Halogen free,non toxic
- For SS316L - Please affix L at the end of Item No.



Item No.	Width		Length		Thickness		Max. Bundle Dia.		Min. Bundle Dia.		Min. Tensile Strength	
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	LBS
Standard Cross Section												
LTBLC-4.6x100	4.6	0.18	100	3.9	0.25	0.010	25	1.00	12.7	0.50	1000	225
LTBLC-4.6x150			150	5.9			37	1.46				
LTBLC-4.6x200			200	7.9			50	1.97				
LTBLC-4.6x250			250	9.8			63	2.48				
LTBLC-4.6x300			300	11.8			76	2.99				
LTBLC-4.6x350			350	13.8			89	3.50				
LTBLC-4.6x360			360	14.2			95	3.74				
LTBLC-4.6x400			400	15.7			105	4.13				
LTBLC-4.6x450			450	17.7			115	4.53				
LTBLC-4.6x500			500	19.7			128	5.04				
LTBLC-4.6x520			520	20.5			135	5.31				
LTBLC-4.6x550			550	21.7			141	5.55				
LTBLC-4.6x600			600	23.6			160	6.30				
LTBLC-4.6x650			650	25.6			167	6.57				
LTBLC-4.6x680			680	26.8			175	6.89				
LTBLC-4.6x700			700	27.5			180	7.09				
LTBLC-4.6x750	750	29.5	185	7.28								
LTBLC-4.6x800	800	31.5	193	7.60								
LTBLC-4.6x840	840	33.1	215	8.46								
LTBLC-4.6x850	850	33.5	220	8.66								
Light-Heavy Cross Section												
LTBLC-6.4x100	6.4	0.25	100	3.9	0.25	0.010	25	1.00	12.7	0.50	1500	350
LTBLC-6.4x150			150	5.9			37	1.46				
LTBLC-6.4x200			200	7.9			50	1.97				
LTBLC-6.4x250			250	9.8			63	2.48				
LTBLC-6.4x300			300	11.8			76	2.99				
LTBLC-6.4x350			350	13.8			89	3.51				
LTBLC-6.4x400			400	15.7			102	4.00				
LTBLC-6.4x450			450	17.7			115	4.50				
LTBLC-6.4x500			500	19.7			128	5.00				
LTBLC-6.4x550			550	21.7			141	5.56				

LTBLC-6.4x600	6.4	0.25	600	23.6	0.25	0.010	160	6.30	12.7	0.50	800	180								
LTBLC-6.4x800			800	31.5			193	7.60												
Heavy Cross Section																				
LTBLC-7.9x100	7.9	0.311	100	3.9	0.25	0.010	25	1.00	12.7	0.50	2220	500								
LTBLC-7.9x150			150	5.9			37	1.46												
LTBLC-7.9x200			200	7.9			50	1.97												
LTBLC-7.9x250			250	9.8			63	2.48												
LTBLC-7.9x300			300	11.8			76	2.99												
LTBLC-7.9x350			350	13.8			89	3.50												
LTBLC-7.9x360			360	14.2			95	3.74												
LTBLC-7.9x400			400	15.7			105	4.13												
LTBLC-7.9x450			450	17.7			115	4.53												
LTBLC-7.9x500			500	19.7			128	5.04												
LTBLC-7.9x520			520	20.5			135	5.31												
LTBLC-7.9x550			550	21.7			141	5.55												
LTBLC-7.9x600			600	23.6			160	6.30												
LTBLC-7.9x650			650	25.6			167	6.57												
LTBLC-7.9x680			680	26.8			175	6.89												
LTBLC-7.9x700			700	27.5			180	7.09												
LTBLC-7.9x750	750	29.5	185	7.28																
LTBLC-7.9x800	800	31.5	193	7.60																
LTBLC-7.9x840	840	33.1	215	8.46																
LTBLC-7.9x850	850	33.5	220	8.66																
Extra-Heavy Cross Section																				
LTBLC-12x350	12	0.47	350	13.8	0.35	0.014	78	3.07	25.4	1.00	3115	700								
LTBLC-12x400			400	15.7			102	4.02												
LTBLC-12x500			500	19.7			128	5.04												
LTBLC-12x600			600	23.6			154	6.06												
LTBLC-12x750			750	29.5			188	7.40												
LTBLC-12x900			900	35.4			228	8.98												
LTBLC-12x1100			1100	43.3			278	10.94												
LTBLC-12.7x350			12.7	0.50			350	13.8					0.35	0.014	78	3.07	25.4	1.00	3115	700
LTBLC-12.7x400	400	15.7			102	4.02														
LTBLC-12.7x500	500	19.7			128	5.04														
LTBLC-12.7x600	600	23.6			154	6.06														
LTBLC-12.7x750	750	27.6			188	7.40														
LTBLC-12.7x900	900	35.4			228	8.98														
LTBLC-12.7x1100	1100	43.3			278	10.94														
Super-Heavy Cross Section																				
LTBLC-15x350	15	0.59	350	13.8	0.35	0.014	78	3.07	25.4	1.00	4100	920								
LTBLC-15x450			450	17.7			108	4.25												
LTBLC-15x600			600	23.6			148	5.83												
LTBLC-15x750			750	29.5			184	7.24												
LTBLC-15x900			900	35.4			220	8.66												
LTBLC-15x1100			1100	43.3			272	10.71												
LTBLC-15.9x350			15.9	0.63			350	13.8					0.35	0.014	78	3.07	25.4	1.00	4100	920
LTBLC-15.9x450							450	17.7							108	4.25				
LTBLC-15.9x600							600	23.6							148	5.83				
LTBLC-15.9x750							750	29.5							184	7.24				
LTBLC-15.9x900	900	35.4			220	8.66														
LTBLC-15.9x1100	1100	43.3			272	10.71														