

## Stainless Steel Cable Ties- Ball-Lock Uncoated Ties

### ► Product Feature

- Ball-Lock type self-lock system, will speed the installation.

### ► Technical Information

- Material: Stainless Steel Grade 304 or 316
- Working Temp.: -80°C to 538°C
- Description: Entirely metallic
- Flammability: Fireproof
- Other Properties: UV-resistant.



Item No.	Width		Length		Thickness		Max. Bundle Dia.		Min. Bundle Dia.		Min. Tensile Strength		Recommended Installation Tool
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs	
<b>Standard Cross Section</b>													
SSU-3.8*100	3.8	0.15	100	3.9	0.26	0.010	25	1.00	12.7	0.50	600	135	LQD-S LQG LBG
SSU-3.8*150			150	5.9			37	1.46					
SSU-3.8*200			200	7.9			50	1.97					
SSU-3.8*250			250	9.8			63	2.50					
SSU-3.8*300			300	11.8			76	3.00					
SSU-3.8*350			350	13.8			89	3.51					
SSU-3.8*400			400	15.7			102	4.00					
SSU-3.8*450			450	17.7			115	4.50					
SSU-3.8*500			500	19.7			128	5.00					
SSU-4.6*100			4.6	0.18			100	3.9					
SSU-4.6*150	150	5.9			37	1.46							
SSU-4.6*200	200	7.9			50	1.97							
SSU-4.6*250	250	9.8			63	2.50							
SSU-4.6*300	300	11.8			76	3.00							
SSU-4.6*350	350	13.8			89	3.51							
SSU-4.6*400	400	15.7			102	4.00							
SSU-4.6*450	450	17.7			115	4.50							
SSU-4.6*500	500	19.7			128	5.00							
SSU-4.6*550	550	21.7			141	5.56							
SSU-4.6*650	650	25.6	167	6.58									
SSU-4.6*800	800	31.5	193	7.60									
<b>Light-Heavy Cross Section</b>													
SSU-6.4*150	6.4	0.25	150	5.9	0.26	0.010	37	1.46	12.7	0.50	1500	350	LQD-S LQG LBG
SSU-6.4*200			200	7.9			50	1.97					
SSU-6.4*250			250	9.8			63	2.50					
SSU-6.4*300			300	11.8			76	3.00					
SSU-6.4*350			350	13.8			89	3.51					
SSU-6.4*400			400	15.7			102	4.00					
SSU-6.4*450			450	17.7			115	4.50					
SSU-6.4*500			500	19.7			128	5.00					
SSU-6.4*550			550	21.7			141	5.56					
SSU-6.4*600			600	23.6			160	6.30					

Item No.	Width		Length		Thickness		Max. Bundle Dia.		Min. Bundle Dia.		Min. Tensile Strength		Recommended Installation Tool
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs	
<b>Heavy Cross Section</b>													
SSU-7.9*150	7.9	0.31	150	5.9	0.26	0.010	37	1.46	12.7	0.50	2220	500	LQD-S LQG LBG
SSU-7.9*200			200	7.9			50	1.97					
SSU-7.9*250			250	9.8			63	2.50					
SSU-7.9*300			300	11.8			76	3.00					
SSU-7.9*350			350	13.8			89	3.50					
SSU-7.9*400			400	15.7			102	4.00					
SSU-7.9*450			450	17.7			115	4.50					
SSU-7.9*500			500	19.7			128	5.00					
SSU-7.9*550			550	21.7			141	5.56					
SSU-7.9*600			600	23.6			154	6.07					
SSU-7.9*650			650	25.6			167	6.58					
SSU-7.9*800			800	31.5			193	7.60					
SSU-7.9*1000			1000	39.4			206	8.12					
<b>Extra-Heavy Cross Section</b>													
SSU-12*350	12	0.47	350	13.8	0.35	0.014	78	3.07	25.4	1.00	3115	700	LQD-S
SSU-12*400			400	15.7			102	4.02					
SSU-12*500			500	19.7			128	5.04					
SSU-12*600			600	23.6			154	6.06					
SSU-12*750			750	29.5			188	7.40					
SSU-12*900			900	35.4			228	8.98					
SSU-12*1100			1100	43.3			278	10.94					
SSU-12.7*350	12.7	0.50	350	13.8	0.35	0.014	78	3.07	25.4	1.00	3115	700	LQD-S
SSU-12.7*400			400	15.7			102	4.02					
SSU-12.7*500			500	19.7			128	5.04					
SSU-12.7*600			600	23.6			154	6.06					
SSU-12.7*750			700	27.6			188	7.40					
SSU-12.7*900			900	35.4			228	8.98					
SSU-12.7*1100			1100	43.3			278	10.94					
<b>Super-Heavy Cross Section</b>													
SSU-15*350	15	0.59	350	13.8	0.35	0.014	78	3.07	25.4	1.00	4100	920	LQD-S
SSU-15*450			450	17.7			108	4.25					
SSU-15*600			600	23.6			148	5.83					
SSU-15*750			750	29.5			184	7.24					
SSU-15*900			900	35.4			220	8.66					
SSU-15*1100			1100	43.3			272	10.71					
SSU-15.9*350	15.9	0.63	350	13.8	0.35	0.014	78	3.07	25.4	1.00	4100	920	LQD-S
SSU-15.9*450			450	17.7			108	4.25					
SSU-15.9*600			600	23.7			148	5.83					
SSU-15.9*750			750	27.6			184	7.24					
SSU-15.9*900			900	31.5			220	8.66					
SSU-15.9*1100			1100	39.4			272	10.71					

- Other lengths available, contact STEMCO Customer Service.
- For information on installation tools, refer to Hand Tools pages.
- Please add the material grade by the end of the item number.